



LE1700 STANDARD TABLET PC

PRODUCT SPECIFICATIONS



Chassis	<ul style="list-style-type: none"> Polycarbonate - upper bezel Magnesium Alloy - lower bezel 	Weight	<ul style="list-style-type: none"> 3.3 lbs. with Standard Battery¹ 4.3 lbs. with Extended Battery²
Operating Systems	<ul style="list-style-type: none"> Microsoft® Windows® XP Tablet PC Edition 2005 Microsoft® Windows Vista™ Business 	Batteries	<ul style="list-style-type: none"> Standard Battery <ul style="list-style-type: none"> Lithium-ion battery with 38.5Whr capacity Battery Life: ~3 hours Optional Extended Battery <ul style="list-style-type: none"> Lithium-polymer with 40Whr capacity Combined battery capacity Maximum 78.5Whr Battery life: ~6-7 hours
Processors/Cache	<ul style="list-style-type: none"> Intel® Core™ 2 Duo Processor Low Voltage L7400 (4MB of L2 cache, 1.5GHz, 667MHz FSB) Intel® Core™ Solo Processor Ultra Low Voltage U1400 (2MB L2 cache, 1.2GHz, 533MHz FSB) 	Battery Charging Times	<ul style="list-style-type: none"> Standard Battery only <ul style="list-style-type: none"> 1.5 hours (Tablet PC on/off)³ Standard Battery with Extended Battery attached <ul style="list-style-type: none"> 3.5 hours (Tablet PC on/off)³
Chipset	<ul style="list-style-type: none"> Intel® 945GM Express 	System Status LEDs	<ul style="list-style-type: none"> Power on/off Battery status
Display Options	<ul style="list-style-type: none"> 12.1" SXGA+ display 12.1" SXGA+ View Anywhere® display 12.1" XGA View Anywhere display 	Control Buttons	<ul style="list-style-type: none"> One 5-way directional control button One function button, one programmable escape button and two programmable buttons Secure Attention Sequence (SAS) button Wireless on/off button
Graphics	<ul style="list-style-type: none"> Intel® Graphics Media Accelerator 950 	AC Adapter	<ul style="list-style-type: none"> 50W universal, 3-pin jack 100-240V 1.5a, 50-60Hz
Video RAM	<ul style="list-style-type: none"> Maximum 224MB total with Intel Dynamic Video Memory Technology 	System Software	<ul style="list-style-type: none"> Motion Dashboard control panel Motion/Softex OmniPass™ Security software Infiniteon Security Platform Tools Toshiba Bluetooth Software Adobe® Acrobat® Reader Windows Journal Sticky Notes Pen/button-based setup utility
Audio Controller	<ul style="list-style-type: none"> Intel® High Definition Audio 	Environmental	<ul style="list-style-type: none"> Temperature <ul style="list-style-type: none"> Operation: +5°C to +35°C Storage: -20°C to +60°C Humidity <ul style="list-style-type: none"> Operating humidity: 8% to 80% without condensation Storage humidity: 8% to 90% without condensation Altitude <ul style="list-style-type: none"> Operation: sea level 0 to 10K ft. Storage: sea level 0 to 40K ft.
PC Card Controller	<ul style="list-style-type: none"> Industry-standard CardBus controller 	Standards	<ul style="list-style-type: none"> ACPI 2.0 compliant
System Memory	<ul style="list-style-type: none"> Base RAM: 1GB (2 x 512MB) 667MHz DDR2 memory with Dual Channel memory support Upgradeable to a maximum of 4GB 	Regulatory	<ul style="list-style-type: none"> AS/NZS 3548:1995 FCC Part 15 Subpart B Class B FCC Part 15 Subpart C FCC part 15 Subpart E FCC part 22 H FCC part 24 E FCC OET65 Supplement C (01-01) CAN/CSA RSS-102 Safety Code 6 CAN/CSA ICES-003 Class B CAN/CSA RSS-210 Industry Canada: RSS-133 Industry Canada: RSS-129 CE: EN55011, EN55022, EN55024, EN301-489-17, EN301-893, EN300-328 CE: R&TTE (89/336/EC) & R&TTE (99/5/EC) CE: EN 50392:2004 / IEC 62209-1:2005
System Storage	<ul style="list-style-type: none"> 1.8" Hard Disk Drive (HDD) with 40GB or 80GB capacities PCI bus master enhanced IDE Supports Ultra ATA 66/100 4200 RPM 	Safety	<ul style="list-style-type: none"> UL, CUL, TUV (EN/IEC 60950-1 A11/2004)
Communications	<ul style="list-style-type: none"> Integrated UMTS Unlocked HSDPA 3.6 Mbps Novatel Wireless EU870D Wireless Wide Area Network Module Intel PRO/Wireless 3945 a/b/g card Integrated 10/100/1000 Ethernet LAN controller with RJ-45 connector (Gigabit Ethernet) Integrated Bluetooth® 	Warranty	<ul style="list-style-type: none"> Standard 1-year warranty Multi-year options available
Audio	<ul style="list-style-type: none"> Motion Speak Anywhere® technology Multi-directional array microphone design intelligently switches between two of the three microphones based on screen orientation Knowles Acoustics IntelliSonic software Two integrated speakers 		
I/O Ports	<ul style="list-style-type: none"> Microphone-in Headphone-out Two USB 2.0 ports DVI-D custom connector IrDA port External VGA port Motion accessory port RJ-45 connector Docking connector DC power in 		
Expansion Card Slots	<ul style="list-style-type: none"> Secure Digital (SD) slot One Type I or Type II PC card slot SIM card slot 		
Security	<ul style="list-style-type: none"> Integrated Fingerprint Reader TCG Trusted Platform Module (TPM) Universal lock slot Motion DataGuard™ 		
Dimensions	<ul style="list-style-type: none"> 11.65" x 9.64" x 0.74" - 0.87" (296mm x 245mm x 18.7 - 22mm) 		

**For more information and localized websites,
please visit www.MotionComputing.com**

¹Weight represents approximate system weight measured with a 38.5Whr battery, empty PCMCIA slot and no pen. Actual system weight may vary depending on component and manufacturing variability.

²Weight represents approximate system weight measured with both the 38.5Whr Standard Battery and a 40Whr Extended Battery attached, empty PCMCIA slot and no pen. Actual system weight may vary depending on component and manufacturing variability.

³Approximate charging time. Validated charging from 5% to 90% with system on or system off.